



N blue 4Season



Inch	Size	Load Index & Speed Symbol	Code	Max. Psi	Max. Load		Rim		Section Width		Overall Diameter		Tread Depth		SLR	S/W	UTQG			E Mark	Mud Snow
					lbs	kgs	Measuring	Approved	mm	inch	mm	inch	mm	/32"			Wear	Trac.	Temp.		
17	225/45R17	94 V XL	15315	50	1,477	670	7.5	7.0-8.5	225	8.9	634	25.0	8.1	10.2/32	295	BS	300	A	A	E	M+S
	225/50R17	94 V	15317	51	1,477	670	7.0	6.0-8.0	233	9.2	658	25.9	8.1	10.2/32	305	BS	300	A	A	E	M+S
		98 V XL	15318	50	1,653	750	7.0	6.0-8.0	233	9.2	658	25.9	8.1	10.2/32	305	BS	300	A	A	E	M+S
	215/60R17	96 H	15333	44	1,565	710	6.5	6.0-7.5	221	8.7	690	27.2	7.9	10/32	317	BS	300	A	A	E	M+S
16	225/55R16	95 H	15323	51	1,521	690	7.0	6.0-8.0	233	9.2	654	25.7	7.9	10/32	300	BS	300	A	A	E	M+S
	215/55R16	97 V XL	15322	50	1,609	730	7.0	6.0-7.5	226	8.9	642	25.3	7.9	10/32	295	BS	300	A	A	E	M+S
	205/55R16	91 H	15274	51	1,356	615	6.5	5.5-7.5	214	8.4	632	24.9	8.1	10.2/32	291	BS	300	A	A	E	M+S
		94 V XL	15275	50	1,477	670	6.5	5.5-7.5	214	8.4	632	24.9	8.1	10.2/32	291	BS	300	A	A	E	M+S
		94 H XL	15265	50	1,477	670	6.5	5.5-7.5	214	8.4	632	24.9	8.1	10.2/32	291	BS	300	A	A	E	M+S
	195/55R16	91 H XL	15321	50	1,356	615	6.0	5.5-7.0	201	7.9	620	24.4	7.9	10/32	286	BS	300	A	A	E	M+S
	215/60R16	95 H	15332	44	1,521	690	6.5	6.0-7.5	221	8.7	664	26.1	7.9	10/32	304	BS	300	A	A	E	M+S
	205/60R16	96 H XL	15331	50	1,565	710	6.0	5.5-7.5	209	8.2	652	25.7	7.9	10/32	299	BS	300	A	A	E	M+S
15	215/65R16	98 H	15342	44	1,653	750	6.5	6.0-7.5	221	8.7	686	27.0	7.9	10/32	312	BS	300	A	A	E	M+S
	195/50R15	82 H	15316	51	1,047	475	6.0	5.5-7.0	201	7.9	577	22.7	7.9	10/32	267	BS	300	A	A	E	M+S
	195/55R15	85 H	15320	51	1,135	515	6.0	5.5-7.0	201	7.9	595	23.4	7.9	10/32	274	BS	300	A	A	E	M+S
	185/55R15	82 H	15319	51	1,047	475	6.0	5.0-6.5	194	7.6	585	23.0	7.9	10/32	270	BS	300	A	A	E	M+S
	205/60R15	91 H	15330	44	1,356	615	6.0	5.5-7.5	209	8.2	627	24.7	7.9	10/32	286	BS	300	A	A	E	M+S
	195/60R15	88 H	15329	44	1,235	560	6.0	5.5-7.0	201	7.9	615	24.2	7.9	10/32	282	BS	300	A	A	E	M+S
	185/60R15	88 H XL	15327	50	1,235	560	5.5	5.0-6.5	189	7.4	603	23.7	7.9	10/32	277	BS	300	A	A	E	M+S
	195/65R15	91 V	15272	44	1,356	615	6.0	5.5-7.0	201	7.9	635	25.0	8.1	10.2/32	289	BS	300	A	A	E	M+S
		91 T	15271	44	1,356	615	6.0	5.5-7.0	201	7.9	635	25.0	8.1	10.2/32	289	BS	300	A	A	E	M+S
		91 H	15264	44	1,356	615	6.0	5.5-7.0	201	7.9	635	25.0	8.1	10.2/32	289	BS	300	A	A	E	M+S
		95 T XL	15273	50	1,521	690	6.0	5.5-7.0	201	7.9	635	25.0	8.1	10.2/32	289	BS	300	A	A	E	M+S
	185/65R15	88 H	15341	44	1,235	560	5.5	5.0-6.5	189	7.4	621	24.4	8.1	10.2/32	284	BS	300	A	A	E	M+S
		88 T	15340	44	1,235	560	5.5	5.0-6.5	189	7.4	621	24.4	8.1	10.2/32	284	BS	300	A	A	E	M+S
14	175/65R15	84 T	15338	44	1,102	500	5.0	5.0-6.0	177	7.0	609	24.0	7.9	10/32	279	BS	300	A	A	E	M+S
	195/60R14	86 T	15328	44	1,168	530	6.0	5.5-7.0	201	7.9	590	23.2	7.9	10/32	269	BS	300	A	A	E	M+S
	185/60R14	82 T	15325	44	1,047	475	5.5	5.0-6.5	189	7.4	578	22.8	7.9	10/32	264	BS	300	A	A	E	M+S
		82 H	15326	44	1,047	475	5.5	5.0-6.5	189	7.4	578	22.8	7.9	10/32	264	BS	300	A	A	E	M+S
	165/60R14	75 H	15324	44	853	387	5.0	4.5-6.0	170	6.7	554	21.8	7.9	10/32	255	BS	300	A	A	E	M+S
	185/65R14	86 T	15339	44	1,168	530	5.5	5.0-6.5	189	7.4	596	23.5	7.9	10/32	271	BS	300	A	A	E	M+S
	175/65R14	82 T	15337	44	1,047	475	5.0	5.0-6.0	177	7.0	584	23.0	7.9	10/32	267	BS	300	A	A	E	M+S
	165/65R14	79 T	15335	44	963	437	5.0	4.5-6.0	170	6.7	570	22.4	7.9	10/32	261	BS	300	A	A	E	M+S
13	155/65R14	75 T	15334	44	853	387	4.5	4.5-5.5	157	6.2	558	22.0	7.6	9.6/32	257	BS	300	A	A	E	M+S
	175/70R14	84 T	15345	44	1,102	500	5.0	4.5-6.0	177	7.0	602	23.7	7.9	10/32	274	BS	300	A	A	E	M+S
	175/65R13	80 T	15336	44	992	450	5.0	5.0-6.0	177	7.0	558	22.0	7.9	10/32	254	BS	300	A	A	E	M+S
	175/70R13	82 T	15344	44	1,047	475	5.0	4.5-6.0	177	7.0	576	22.7	7.9	10/32	261	BS	300	A	A	E	M+S
	155/70R13	75 T	15343	44	853	387	4.5	4.0-5.0	157	6.2	548	21.6	7.6	9.6/32	250	BS	300	A	A	E	M+S

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- All figures are for reference; our company is not responsible for printing errors.

NEXEN NEXEN TIRE

NEXEN TIRE EUROPE GMBH | MERGENTHALERALLEE 79-81, D-65760 ESCHBORN TS, GERMANY [Like NEXEN TIRE Europe GmbH](#)
T +49-6196-95486-0 F +49-6196-95486-77 de.nexentire.com

SALES HEADQUARTER | NEXEN TIRE 4F 226, BANGBAE-RO, SEOCHO-GU, SEOUL, KOREA 137-830
T +82-2-3476-2782 F +82-2-3476-2205 www.nexentire.com

NEXENTIRE [Facebook](#) Fanpage



Driving Tomorrow

2017 NEW PRODUCT

N blue 4Season
EUROPEAN ALL WEATHER



NEXEN NEXEN TIRE



High Performance All Weather Tire for Passenger Cars!

N blue 4Season Key Performance


Maximized Wet Performance

Maximized wet performance with optimized combination of new generation solution-SBR and high grip resin to improve wet braking and handling.


NEW GENERATION SOLUTION-SBR



HIGH GRIP RESIN



Wet Braking




Balanced Snow Performance

New tread compound provides well balanced performance by using fine grade and applying a high content of silica with new mixing process.



IMPROVED SNOW BRAKING



Snow Braking




All Season Performance

To achieve all season performance of tire, controlled dynamic properties of compound provides harmony of stiffness and flexibility over a wide temperature range.

SPECIAL POLYMER & FILLER COMBINATION



STIFFNESS CONTROL




N blue 4Season



Pattern Design & Construction

Round & V Type Groove

Optimized directional pattern design for better drainage improves aquaplaning & snow slush performance.




3D Sipe

Well balanced block stiffness provides better snow traction and dry stability for more safety under all type of road and weather conditions.



Multi-Season Sipe



3D-winter sipe in center / summer sipe in shoulder provides outstanding snow traction and cornering performance as well as extraordinary wet grip performance to secure best performance under all weather condition.

High Modulus Carcass

Minimizes tire deformation and helps maintain the tire's shape to enhance driving stability with OCCS technology.


OCCS Optimized Carcass Contour System

High Tensile Steel Belts

Enhance braking function with optimized grip pressure and stress dispersion by OBCS technology.

OBCS Optimized Best Contour System

Performance Radar Chart



N blue 4Season has significantly improved braking and handling in wet and snowy road than N'Priz 4S.

N blue 4Season
N'Priz 4S (Conventional)

※ Test Size : 205/55R16

Magazine Test Result

"Recommendable" in Autonavigator(Hungary)



Product	Rating	Weighted result [%]
Michelin CrossClimate	good	97.2%
Nexen N'blue 4Season	satisfying	93.9%
Goodyear Vector 4 Season	satisfying	91.2%

Very Good Performance on Dry & Wet !

#Braking distance on dry and wet asphalt (60km/hr)

Evaluation / Product category	Michelin Cross Climate	NEXEN TIRE N'blue 4Season	Goodyear Vector 4 Season
Dry	14.40m	14.90m	15.80m
Wet	16.70m	17.30m	17.30m
Average	15.55m	16.10m	16.55m

Sources : Autonavigator Magazine in Hungary, 2016/8

NEXEN NEXEN TIRE